

THE KEY TO MAKING A GOOD IMPRESSION!

LET IT FLOW. MAKE AN IMPRESSION WITH MORE THAN CATCHY TEXT: DELIVER FAST, IMPRESSIVE RESULTS. TAKE ADVANTAGE OF THE MANY POSSIBILITIES THE NEW 3555i, 4555i AND 5555i A3 B/W MULTIFUNCTIONAL SYSTEMS HAVE TO OFFER FOR COPYING, PRINTING, SCANNING OR FAXING*. ORGANISE YOUR DOCUMENTS AND PRINT JOBS AND PROTECT YOUR DATA AGAINST UNAUTHORISED ACCESS.

LOOKING FOR EVEN MORE CONVENIENCE? OPTIMISE YOUR SYSTEM TO YOUR EXACT REQUIREMENTS WITH OPTIONAL HARDWARE AND SOFTWARE FUNCTIONS. LEAVE A LASTING POSITIVE IMPRESSION ON YOUR CUSTOMERS AND BUSINESS PARTNERS.



HIGHLIGHTS:



Intelligent paper management: Benefit from maximum flexibility thanks to a paper capacity of up to 7,150 sheets from six paper feeds*. Various paper types, tab sheets, special formats up to A3+, banner paper and paper weights up to 300 g/m² are no problem at all. Successful presentations, handouts and brochures are a piece of cake thanks to the finishing* options.



Customised functions: It is easy to integrate optional software solutions for scanning, productivity, security and archiving using the HyPAS interface – all in exact accordance with your individual needs. Additional solutions for Follow-Me-Printing* in the network or creating text-searchable documents* when scanning help you save time and effort.



Create documents fast: Very short warm-up times and output of the first copy after 4.7/3.8/3.2 seconds (3555i/4555i/5555i), high-speed output of up to 55 A4 pages per minute or up to 27 A3 pages per minute (5555i), and 100% duplex productivity ensure fast results, meeting the deadline.



Protect the environment: Reduce energy consumption by using 'Deep Sleep' mode and only activate the functions you really need. Good for the environment and your budget.

DIGITAL 
MULTIFUNCTIONAL SYSTEM

3555i / 4555i / 5555i

Copy / Print / Scan / Fax

A3

TECHNICAL DATA

| General | | Print system | | Optional fax system (W) B | |
|------------------------------|--|---------------------------|--|---------------------------|---|
| Type | Desktop | Type | Integrated within the system | Fax memory | 12 MB (max 120 MB) |
| Function | Copy, print, scan, optional: fax | Print format | A6R-A3+ | Abbreviated dial | 2,000 numbers |
| Print technology | Laser b/w | Print resolution | 600 x 600 dpi, 9,600 x 600 dpi level | One touch dial | 1,000 numbers |
| Original format | max A3 from platen glass | Processor | Freescale QorIQ P1022 (Dual Core) 800 MHz | Group dial | 500 numbers |
| Copy/print speed | 3555i: max 35 A4 pages/min and max 17 A3 pages/min 4555i: max 45 A4 pages/min and max 22 A3 pages/min, 5555i: max 55 A4 pages/min and max 27 A3 pages/min, | Interfaces | USB 2.0, 10/100/1000BaseTX, USB host | Operating systems | Windows XP, Vista, Windows 7/8/8.1, Server 2003/2008 R2/2012 R2 |
| 1st page (copy/print) | 4.7/6.0 seconds* (3555i), 3.8/5.3 seconds* (4555i), 3.2/4.9 seconds* (5555i) | Network protocols | TCP/IP, IPX/SPX, Net BEUI | Functions | Network fax driver, automatic redialling, delayed transmission, max 2 fax kits for parallel transmission and reception |
| Warm-up time | 23 seconds | Operating systems | Windows XP, Vista, Windows 7/8/8.1, Server 2003/2008 R2/2012 R2, Novell NetWare, Linux, Mac ex OS 10.4 | | |
| Copy resolution | 600 x 600 dpi, 9,600 x 600 dpi level | Emulations | PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIc | | |
| Greyscales | 256 | Functions | PDF/XPS direct printing, printing of e-mails, private printing, barcode printing | | |
| Paper feed | 2 x 500 sheet universal cassettes (A5R-A3+ [max 305 x 457 mm]), 150 sheet multi-bypass (A6R-A3+, Banner [305 x 1,219 mm]), A3+ only for printing | | | | |
| Paper weights | Universal cassette 60-220 g/m ² , multi-bypass 60-300 g/m ² , duplex 60-256 g/m ² | | | | |
| Paper output | 250 sheet A4 | | | | |
| System memory | 2,048 MB RAM, min 160 GB HDD** | | | | |
| Continuous copying | 1-999 copies | | | | |
| Zoom | 25%-400% in steps of 1% | | | | |
| Functions | Adjustable touch screen, duplex, 1,000 management codes, multi tasking controller, direct printing from USB stick, etc. | | | | |
| Dimensions/Weight | | Scan system | | Options | |
| Dimensions | 747 x 648 x 767 mm (H x W x D) | Scan type | CCD colour and b/w | Original feeder | DP-770 (B) document processor with automatic reverse function (A5R-A3, capacity: 100 sheet A4, paper weight 45-160 g/m ²), DP-772 document processor with simultaneous duplex scanning (A6R-A3, capacity: 175 sheet A4, paper weight 35-220 g/m ² [A5R-A3]) |
| Weight | approx. 86 kg | Scan format | max A3 | Platen cover | Platen cover type E (if document processor is not installed) |
| | | Scan speed | b/w: max 80/160 A4 originals/min (simplex/duplex), colour: max 50/80 A4 originals/min (simplex/duplex) with DP-772 (300 dpi) | Finisher | DF-770 (C) (capacity: 1,000 sheet A4, stapling max 50 sheet A4), DF-790 (C) (capacity: 4,000 sheet A4, stapling max 65 sheet A4), PH-7C hole punch unit for DF-770 (C)/790 (C), BF-730 brochure module for DF-790 (C) (max 16 sheet saddle stitching and folding A4/A3, tri-folding max 5 sheet A4), MT-730 (B) multi tray for DF-790 (C) |
| | | Scan resolution | 200 dpi, 300 dpi, 400 dpi, 600 dpi | Job Separator | JS-732 (inner): 100 sheet, JS-731 (outer): 70 sheet |
| | | Scan mode | Photo, text, photo/text, OCR | Paper feed | PF-730 (B) (2 x 500 sheet universal cassettes [A5R-A3+]), PF-740 (B) (2 x 1,500 sheet large capacity cassette [A4]), PF-770 (3,000 sheet large capacity tray [A4], side deck) |
| | | File types | TIFF, PDF, PDF/A, JPEG, XPS | Other options | Scan extension kit (A), Data security kit (E), Internet fax kit (A), Printed document guard kit (B), Card authentication kit (B), Card reader holder (E), Keyboard holder (B), Banner guide (A), UG-33 ThinPrint® kit, UG-34 Emulation option kit, IB-50 Gigabit Ethernet card, IB-51 WLAN card, DT-730 (B) Document tray, cabinet no. 63 |
| | | Interface | 10/100/1000BaseTX | | |
| | | Network protocol | TCP/IP | | |
| | | Operating systems | Windows XP, Vista, Windows 7/8, Server 2003/2008 R2/2012 | | |
| | | Functions | Scan to SMB, scan to e-mail, scan to FTP, scan to USB, TWAIN scan, WIA scan (Windows Vista, Windows 7/8, Server 2008 R2/2012), SMTP authentication, LDAP, PDF compression and encryption | | |
| Environment | | Optional fax system (W) B | | | |
| Mains voltage | 220/240 V, 50/60 Hz | Compatibility | Super G3 | | |
| Power consumption | approx. 1,800 W max, approx. 660/780/890 W (3555i/4555i/5555i) in operation, approx. 170 W in stand-by mode, approx. 8.5 W in sleep mode | Original format | max A3 | | |
| Safety | GS/TÜV, CE | Modem speed | 33.6 kbps | | |
| | | Transmission speed | 3 seconds or less using JBIG | | |
| | | Compression method | JBIG, MMR, MR, MH | | |
| | | Fax resolution | Standard (200 x 100 dpi), fine (200 x 200 dpi), super fine (200 x 400 dpi), ultra fine (400 x 400 dpi), 600 x 600 dpi | | |

* Depending on operating status.

** For copy, print, scan, fax.

Specifications subject to change without notice.

Image shows machine with optional accessories.

The 3555i, 4555i and 5555i are manufactured in accordance with the requirements of the Energy Star Program.



HyPAS™

UTAX GmbH has been a trade mark for professional office technology since 1961. As the partner of a German wide dealer network and international distribution, we are specialized in the distribution and integration of printing, copying and multifunctional systems in corporate IT and public sector, amongst others. With the MDS solution UTAX smart for example, output systems can be controlled regardless of the manufacturer and the infrastructure can be optimised in line with demands.

UTAX recommends the use of original UTAX accessories for trouble-free operation of your system. For recommended print media refer to the user manual. UTAX and the UTAX logo are registered trade marks of UTAX GmbH. All other brand names referred to are registered trade marks of the respective manufacturers.

Your UTAX dealer