

FRESH COLOURS, FAST **PRINTING – JUST LIKE THAT!**

COLOUR HAS ARRIVED - HOW ABOUT A WAGER ON THAT? SEE FOR YOURSELF WITH THE NEW 4505ci AND 5505ci A3 COLOUR MULTIFUNCTIONAL SYSTEMS: SIMPLY CHOOSE THE MOST EYE-CATCHING COLOURS FROM THE WHOLE RANGE. IT MAKES NO DIFFERENCE IF IT'S A PHOTOGRAPH OR BACKGROUND, THE QUALITY OF THE RESULT IS EXTREMELY IMPRESSIVE.

YOUR WORKFLOW IS FAST, STRAIGHTFORWARD AND SECURE THANKS TO THE MANY OPTIONS TO PRINT AND SCAN – INCLUDING ON THE GO VIA WI-FI –, COPY OR FAX*, AND IF THAT'S NOT ENOUGH, YOU CAN OPTIMISE YOUR SYSTEM WITH OPTIONAL HARDWARE AND SOFTWARE FUNCTIONS THAT MEET YOUR INDI-VIDUAL REQUIREMENTS EXACTLY. JUST LIKE THAT. THE WAGER IS WON!



DIGITAL S S S S MULTIFUNCTIONAL COLOUR SYSTEM 4505ci / 5505ci Copy / Print / Scan / Fax Α3

HIGHLIGHTS:

Positive image effect: Improve your communications and make an impression with visually appealing colour documents. Score points with your customers and business partners thanks to high-quality printing and copies. Even larger print runs are created in a productive and reliable manner. Consistent colours, the use of different colour tables and colour management with the Fiery® Controller* guarantee noticeably better colour quality.



Intelligent paper management: Benefit from maximum flexibility for larger volumes thanks to paper capacities of up to 7,650 sheets from eight paper feeds* for various paper types. Print tab sheets, special formats up to A3+, banner paper and paper weights up to 300 g/m². Create professional brochures or letters with tri-folding in a flash using the versatile finishing* options.

Create documents fast: Short warm-up times and output of the first colour copy after 5.1/4.7 seconds (4505ci/5505ci), highspeed output of up to 50 A4 colour pages per minute (5505ci) and 100% duplex productivity ensure fast, high-quality results, on schedule without being pushed for time. Use the optional dual scan feed to scan double-sided documents at up to 160 pages per minute, allowing you to keep your originals in excellent condition.

Customised functions: It is easy to integrate optional software solutions for scanning, productivity, security and archiving using the HyPAS interface - all in exact accordance with your individual needs. Optimise your workflows by creating text-searchable documents* or using Follow-Me-Printing* in the network.

4505ci / 5505ci

TECHNICAL DATA

General	
Туре	Desktop
Function	Copy, print, scan, optional: fax
Print technology	Laser colour and b/w
Original format	max A3 from platen glass
Copy/print speed	<i>4505ci:</i> max 45 A4 pages/min and max 22 A3 pages/min in colour and b/w
	5505ci: max 50 A4 pages/min and max 25 A3 pages/min in colour and max 55 A4 pages/min and max 27 A3 pages/min in b/w
1st page (copy/ print)	Colour: 5.1/6.6 seconds*, b/w: 3.9/5.4 seconds* (4505ci),
	Colour: 4.7/6.2 seconds*, b/w: 3.4/4.9 seconds* (5505ci)
Warm-up time	30 seconds
Copy resolution	600 x 600 dpi, 9,600 x 600 dpi level
Greyscales	256
Paper feed	2 x 500 sheet universal cassettes (A5R-A3+ [max 305 x 457 mm]), 150 sheet multi-bypass (A6R-A3+, Banner [305 x 1,219 mm]), A3+ only for printing
Paper weights	Universal cassette 60-220 g/m², multi-bypass 60-300 g/m², duplex 60-256 g/m²
Paper output	250 sheet A4
System memory	3.5 GB RAM, 2 x 160 GB HDD**
Continuous copying	1-999 copies
Zoom	25 %-400 % in steps of 1 %
Functions	Adjustable touch screen, duplex, 1,000 management codes, multi tasking controlle direct printing from USB stick, colour optimizer for printing, etc.

••••••	•••••••••••••••••••••••••••••••••••••••
Dimensions	747 x 648 x 767 mm (H x W x D)
Weight	approx. 114 kg
Environment	
Mains voltage	220/240 V, 50/60 Hz
Power consumption	approx. 1,800 W max, approx. 1,030 W

	(4505ci)/1,140 W (5505ci) in operation, approx. 200 W in stand-by mode, approx. 10.7 W in sleep mode
Safety	gs/tüv, ce

Print system

Туре	Integrated within the system
Print format	A6R-A3+
Print resolution	600 x 600 dpi, 9,600 x 600 dpi level
Processor	Freescale QorlQ P1022 (Dual Core) 1.067 MHz
Interfaces	USB 2.0, 10/100/1000BaseTX, USB host
Network protocols	TCP/IP, IPX/SPX, Net BEUI
Operating systems	Windows XP, Vista, Windows 7/8/8.1, Server 2003/2008 R2/2012 R2, Novell NetWare, Linux, Mac ex OS 10.4
Emulations	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIc
Functions	PDF/XPS direct printing, printing of e-mails, private printing, barcode printing
Scan system	
Scan type	CCD colour and b/w
Scan format	max A3
	IIIdx A5
Scan speed	max 80/160 A4 originals/min (simplex/ duplex) in colour or b/w with DP-772 (300 dpi)
Scan speed Scan resolution	max 80/160 A4 originals/min (simplex/ duplex) in colour or b/w with DP-772 (300
·	max 80/160 A4 originals/min (simplex/ duplex) in colour or b/w with DP-772 (300 dpi)
Scan resolution	max 80/160 A4 originals/min (simplex/ duplex) in colour or b/w with DP-772 (300 dpi) 200 dpi, 300 dpi, 400 dpi, 600 dpi
Scan resolution Scan mode	max 80/160 A4 originals/min (simplex/ duplex) in colour or b/w with DP-772 (300 dpi) 200 dpi, 300 dpi, 400 dpi, 600 dpi Photo, text, photo/text, OCR
Scan resolution Scan mode File types	max 80/160 A4 originals/min (simplex/ duplex) in colour or b/w with DP-772 (300 dpi) 200 dpi, 300 dpi, 400 dpi, 600 dpi Photo, text, photo/text, 0CR TIFF, PDF, PDF/A, JPEG, XPS

 Operating systems
 Windows XP, Vista, Windows 7/8, Server 2003/2008 R2/2012

 Functions
 Scan to SMB, scan to e-mail, scan to FTP, scan to USB, TWAIN scan, WIA scan (Windows Vista, Windows 7/8, Server 2008 R2/2012), SMTP authentication, LDAP, PDF compression and encryption

Optional fax system (W) B Compatibility Super G3 Original format max A3 Modem speed 33.6 kbps Transmission speed 3 seconds or less using JBIG Compression JBIG, MMR, MR, MH method Standard (200 x 100 dpi), fine (200 x 200 dpi), super fine (200 x 400 dpi), ultra fine (400 x 400 dpi), 600 x 600 dpi



Optional fax system (W) B		
Fax memory	12 MB (max 120 MB)	
Abbreviated dial	2,000 numbers	
One touch dial	1,000 numbers	
Group dial	500 numbers	
Operating systems	Windows XP, Vista, Windows 7/8/8.1, Server 2003/2008 R2/2012 R2	
Functions	Network fax driver, automatic redialling, delayed transmission, max 2 fax kits for parallel transmission and reception	
Options		
Original feeder	DP-770 (B) document processor with aut matic reverse function (ASR-A3, capacity 100 sheet A4, paper weight 45-160 g/m ² DP-772 document processor with simultar eous duplex scanning (A6R-A3, capacity: 175 sheet A4, paper weight 35-220 g/m ² [A5R-A3])	
Platen cover	Platen cover type E (if document process is not installed)	
Finisher	DF-770 (C) (capacity: 1,000 sheet A4, stapling max 50 sheet A4), DF-790 (C) (capacity: 4,000 sheet A4, stapling max 65 sheet A4), PH-7C hole punch unit for DF-770 (C)/790 (C), BF-730 brochure mo ule for DF-790 (C) (max 16 sheet saddle stitching and folding A4/A3, tri-folding max 5 sheet A4), MT-730 (B) multi tray for DF-790 (C)	
Job Separator	JS-732 (inner): 100 sheet, JS-731 (outer): 70 sheet	
Paper feed	max 2 x PF-730 (B) (2 x 500 sheet universal cassettes [A5R-A3+]), max 2 x PF-740 (B) (2 x 1,500 sheet large capacity cassettes [A46]), PF-780 (B) (50 sheet multi-purpose cassette [A5R-A3+], required if two PF-730 (B)/PF-740 (B) are installed), PF-770 (3,000 sheet large capacity tray [A4], side deck)	
Other options	Scan extension kit (A), Data security kit (E), Internet fax kit (A), Printed document guard kit (B), Card authentication kit (B), Card reader holder (E), Keyboard holder (B), Banner guide (A), UG-33 ThinPrint [®] k UG-34 Emulation option kit, IB-50 Gigabit Ethernet card, IB-51 WLAN card, DT-730 (B) Document tray, cabinet no. 63, Fiery [®] Controller	

* Depending on operating status.

** For copy, print, scan, fax.

Specifications subject to change without notice.

Image shows machine with optional accessories.

The 4505ci and the 5505ci are manufactured in accordance with the requirements of the Energy Star Program.



ΗγΡΔ5

UTAX GmbH has been a trade mark for professional office technology since 1961. As the partner of a German wide dealer network and international distribution, we are specialized in the distribution and integration of printing, copying and multifunctional systems in corporate IT and public sector, amongst others. With the MDS solution UTAX smart for example, output systems can be controlled regardless of the manufacturer and the infrastructure can be optimised in line with demands.

UTAX recommends the use of original UTAX accessories for trouble-free operation of your system. For recommended print media refer to the user manual. UTAX and the UTAX logo are registered trade marks of UTAX GmbH. All other brand names referred to are registered trade marks of the respective manufacturers.

www.utax.com

Your UTAX dealer